

Vertical Double Walled 125 Liter Autoclave

QUOTATION S.no	Model	Size	Load	Capacity	Qty	Amount
1	SLV-905 LID Locking Fully SS	25 X 24 Inch	4.0 Kw	125 Liter	1	Fully S.S 304

Including:

Manual:

- Water level indicator
- Stainless steel basket
- Vacuum breaker

Semi-Automatic:

- Water level indicator²
- Stainless steel basket
- Vacuum breaker ²
- Automatic low water cut off system
- Automatic pressure control switch
- PID temperature indicator cum controller

Fully Automatic

- Vacuum breaker.
- Water level indicator.
- Stainless steel basket
- Automatic low water cut off system
- Display: Jumbo LCD 20x 4
- Control: ON/OFF / T.P.
- Input: PT-100 Pressure Sensor for chamber.
- Purging Range: User Settable.
- Sterilization Time: User Settable.
- Post Sterilization-Drying Time: User Settable.
- Boiler Control: User Settable.
- Buzzer: High / Low Alarm/Process End.
- Pressure Display.
- Sterilization cycle process

Technical specification

- Inner chamber, outer chamber and support ring are fully made of stainless steel 304 .
- Heaters cover stand and carrier /bucket are made of SS.
- Lid made of thick machined stainless steel plate.
- Radial locking lid ensures user safety and safe locking.
- Lid is fitted with pressure gauge, spring loaded safety valve, double safety valve, manual exhaust valve, vacuum breaker as a safety device and water level indicator.
- Drain valve facilitates easy cleaning of the chamber.
- Moulded joint less silicon rubber gasket.
- All internal joints are argon arc welded, ground and polished to give crevice free internals.
- Miniature circuit breaker for mains on/off plus safety of control panel.
- Industrial grade energy efficient heaters reduce power bill drastically.

- Sterilizing pressure=1.2kgf/cm²[15psi]at121^oc
- Operating pressure=from 15psi to 22psi
- Power Supply=220×230V AC, 50/60 Hz
- Pressure Vessel= SS 304 Grade Stainless steel
- Sterilizing pressure=1.2kgf/cm²[15psi]at121^oc
- Operating pressure=from 15psi to 22psi
- Power Supply=220×230V AC, 50/60 Hz
- Pressure Vessel= SS 304 Grade Stainless steel

Construction:

- Inner Chamber: SS 304
- Outer Chamber: SS 304
- Lid: SS 304
- Gasket: Silicon joint less
- Ring: SS 304
- Leg Stand: SS 304
- Sheet Thicknes: 3 mm

